
This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

	REVISIONS							
REV	DESCRIPTION	DATE	INITIAL	APPROVED				
Α	ADDED 2.50 REF. DIMENSION TO -1, ALSO ADDED .455 REF. DIMENSION TO -3.	9/24/2009	WP	GE				
1	CH'D -3 HANDLE DIA., WAS Ø 1.20 IS Ø 1.283 REF. DIM455 IS NOW .767.	9/28/2009	WP	GE				
2	REMOVED ENGRAVING FROM -1, CH'D -3 OD, FROM <b>Ø</b> 1,28 TO <b>Ø</b> 1,276, MILLED FLAT FROM .51 TO .587 REF., AND .767 REF. TO .50 REF. ALSO CH'D -3 .032×60 ° TO .03 @ 30 °, AND .08×60 ° TO .08 @ 60 °. ALSO ADDED VISIBLE KNURLING.	10/3/2009	WP	RW				
2A	CH'D WAS CLEAR HARD ANODIZING IS CLEAR ANODIZING AND ADDED KNURL NOTE.	10/27/2010	WP	GE				
2B	SEPERATED TOOLS FROM KIT RBW6205G00331-3G. ADDED AW139 TO USED ON MODEL.	10/17/2013	CFS	RW				



ORIGINAL No. REF.
RBW3205G00331-3G = 3G3205G00331
DO NOT USE, FOR REFERENCE ONLY.

## FUNCTION: USED TO REMOVE AND INSTALL THE MAIN ROTOR BLADE BOLTS.

	ASSY QTY	ASSY QTY	B/O	/O Part # UNIT Description		Description	Material	B/O INFORMATION OR SPECIFICATIONS	
-	GII	QII		,		POLT CUIDE	(0/1	PDW/005000451.00	,
L				-1	ı	BOLT GUIDE	6061	RBW6205G03451-3G	1
				-3	1	PULLER	6061	RBW6205G08451-3G	1
			B/O	-5	1	PISTOL CASE	BLACK PLASTIC	R.S.R. SPORTS #10137	N/S

## ® RED BARN MACHINE

M/R BLADE RETENTION BOLT REM/INSTL TOOL KIT

RBW6205G00331-3G

MAT'L		DRAWN BY:	SMITH		
UNLESS OTHERWISE DIMENSIONS ARE IN	LINCHES	APPROVED D Weil			
.XXX ± .005 FRACTI	ONS ± 1/32	HEAT TREAT			
.XX ± .01 ANO	SLEG I.S	FINISH			
1. BREAK ALL SHARP EDGE	ES .015 x 45°	SPEC			
OR .015R 2. DIMENSIONAL LIMITS AP	DI V AFTED	USED ON MODEL			
PLATING PLATING	LLIACIEN	AGUSTA AW139			
SCALE 1:2	DATE 10/	17/2013	SHEET 1 OF 1		

REV 2B